

## 8FQ7

### Medium-Mu Twin Triode

*The 8FQ7 is the same as the 6FQ7 except for the following items:*

#### Heater Characteristics and Ratings

|                                         |               |   |
|-----------------------------------------|---------------|---|
| Current. . . . .                        | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A . . . . . | 8.4           | V |
| Warm-up time (Average) . . . . .        | 11            | s |

## 8GJ7

### Medium-Mu Triode—Sharp-Cutoff Pentode

*The 8GJ7 is the same as the 6GJ7 except for the following items:*

#### Heater Characteristics and Ratings

|                                        |               |   |
|----------------------------------------|---------------|---|
| Current. . . . .                       | 0.300 ± 0.020 | A |
| Voltage (AC or DC) at 0.300A . . . . . | 8.0           | V |
| Warm-up time (Average) . . . . .       | 11            | s |

## 8GN8

### High-Mu Triode—Sharp-Cutoff Pentode

*The 8GN8 is the same as the 6GN8 except for the following items:*

#### Heater Characteristics and Ratings

|                                         |               |   |
|-----------------------------------------|---------------|---|
| Current. . . . .                        | 0.600 ± 0.040 | A |
| Voltage (AC or DC) at 0.600 A . . . . . | 8.0           | V |
| Warm-up time (Average) . . . . .        | 11            | s |

## 8GU7

### Medium-Mu Twin Triode

*The 8GU7 is the same as the 6GU7 except for the following items:*

#### Heater Characteristics and Ratings

|                                        |               |   |
|----------------------------------------|---------------|---|
| Current. . . . .                       | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A. . . . . | 8.4           | V |
| Warm-up time (Average) . . . . .       | 11            | s |



RADIO CORPORATION OF AMERICA  
Electronic Components and Devices  
Harrison, N. J.

DATA  
7-67